

In-Vehicle Charger for L3Harris XL-95P

Rugged Single Unit

EVC-HA1

For XL-45P | XG-15P | XG-25P | XG-75P
other L3Harris radios



- Tested to 9 g-force and NFPA compliant.
- Radio may stay powered on while charging.
- Includes DC hardwire cable and easy release tie-down strap.
- USB port for charging mobile phones or tablets.
- AMPS pattern with optional dash / floor mounting brackets available.
- Compatible with all L3Harris and Power Products batteries for radios referenced.

Housing Materials	ABS / PC blend with metal support frame
Contact Type	Custom design probe contact for fail-safe battery connection
Operating Temperature	0° C to 45° C / 32° F to 113° F
Charge Rate (Radio Battery)	800 mA
Compatible Chemistries	Li-Ion, LiPo, and NiMH
Input Voltage (Minimum)	12V / 2.8A (minimum for radio battery + USB) / 1.0A (minimum for radio battery only)
USB Charging Port	For Type A connector / 5V output / 2A charge rate
DC Power Cable (EVC-HW)	Included with EVC-HA1, 16AWG / 3m (9.8') length / secure 4-pin connector
Unit Dimensions (W x H x D)	2.7" x 5.3" x 3.0" / 66.3 x 133.9 x 77.2 mm
Unit Weight	0.61 lbs. / 277 g



EVC-HA1-4
Rugged 4-unit model also available.