

In-Vehicle Charger For Kenwood NX-3200

Rugged Single Unit

EVC-KW3

For NX-3300 | NX-3400 | NX-3220 | NX-3320 |
NX-3420 | NX-220 | NX-320 | NX-420 | TK-2170 |
TK-3170 | other Kenwood radios



- Tested to 9 g-force and NFPA compliant.
- Radio may stay powered on while charging.
- Includes DC hardwire cable and easy release tie-down strap.
- USB port for charging mobile phones or tablets.
- AMPS pattern with optional dash / floor mounting brackets available.
- Compatible with all Kenwood and Power Products batteries for radios referenced, including KNB-68LS and KNB-79LCM.

Housing Materials	ABS / PC blend with metal support frame
Contact Type	Custom design probe contact for fail-safe battery connection
Operating Temperature	0° C to 45° C / 32° F to 113° F
Charge Rate (Radio Battery)	800 mA
Compatible Chemistries	Li-Ion, LiPo, and NiMH
Input Voltage (Minimum)	12V / 2.8A (minimum for radio battery + USB) / 1.0A (minimum for radio battery only)
USB Charging Port	For Type A connector / 5V output / 2A charge rate
DC Power Cable (EVC-HW)	Included with EVC-KW3, 16AWG / 3m (9.8') length / secure 4-pin connector
Unit Dimensions (W x H x D)	2.8" x 5.3" x 3.1" / 69.8 x 133.9 x 77.4 mm
Unit Weight	0.62 lbs. / 279 g

LEVCA-M



LEVCA-MHD



EVC-KW3-4
Rugged 4-unit model also available.