


LMR BATTERY SPECIFICATIONS	PART NUMBER
	BPPA4KLI-S

COMPATIBLE RADIOS	L3Harris XL-150P, XL-185P, XL-200P
ALTERNATIVE TO	XL-PA4K / 14035-5050-01 (4800 mAh)
COMPATIBLE CHARGERS	Endura EC1-HA3C, EC1M-HA3C, EC2M-HA3B-D, EC6M-HA3C, EC12M-HA3B-D, EVC-HA3 / L3Harris XL-CH4X, XL-CH4W, XL-CH5A
VOLTAGE	7.2V
CAPACITY	Typical 5000 mAh / 36.0 Wh, minimum 4800 mAh / 34.6 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Samsung INR21700-50E or equivalent
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +45° C (charge)
CHARGE CYCLES	500 (80% capacity at rated minimum, 76% capacity at rated typical)
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for cycle life or maintaining capacity)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP68 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	24 months
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p>Dimensions 76.9 x 58.2 x 28.3 mm 3.03" x 2.29" x 1.11"</p> <p>Weight 189 g / 6.7 oz.</p> </div>